



## Guangzhou Wangli Auto Parts Co., Ltd.



6018ZZNR Bearing 2D drawings and 3D CAD models

90,000 mm x 140,000 mm x 24,000 mm NTN  
6018ZZNR deep groove ball bearings

Bearing No. 6018ZZNR

Size	90x140x24 mm
Bore Diameter	90,000 mm
Outer Diameter	140,000 mm
Width	24,000 mm
d	90,000 mm
D	140,000 mm
B	24,000 mm
C	24,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359336337
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	90MM Bore; 140MM



## Guangzhou Wangli Auto Parts Co., Ltd.

	Outside Diameter; 24MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Other Features	Deep Groove   With Snap Ring   Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Weight / LBS	1.175
Outer Race Width	0.945 Inch   24 Millimeter
Bore	3.543 Inch   90 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	5.512 Inch   140 Millimeter
bore diameter:	90 mm
static load capacity:	49500 N
outside diameter:	140 mm
precision rating:	ISO Class 0
overall width:	24 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Shielded
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	24 mm



## Guangzhou Wangli Auto Parts Co., Ltd.

snap ring included:	With Snap Ring
outer ring width:	24 mm
internal clearance:	CN
maximum rpm (grease):	4700 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	1.5 mm
dynamic load capacity:	58000 N
manufacturer product page:	<a href="#">Click here</a>